LS SLITTER

Application : **Surface type winding, suitable for slitting various fax thermal papers, registered & recording papers.**

Specifications :

Machine Width :	**0.7M/1.0M**	**Max. Unwind O.D :**	**1000mm**
Rewind Core I.D :	**12mm – 50mm**	**Min. Slitting Width :**	**30mm**
Max. Rewind O.D :	**200mm**	**Machine Speed :**	**200M / Min**

Features:

1. **Equipped with separated shaft type unwind base and auto unwind tension controller, which has user friendly operation.**
2. **Rewind is controlled by 3 surface rollers and surface tension is adjustable for different materials and requests.**
3. **Power by A.C motor control, which enable an automatic process from paper adherence to mark making at the end of each finished roll.**
4. **Equipped with 2 sets of mark making devices with choice to print in the front or the back side.**
5. **Equipped with shear cutter, which is suitable for slitting various materials. Trim unit is a suction blower design power by A.C. motor control, which collects waste materials much efficiently.**
6. **Central system is controlled by PLC unit with LCD touch screen, which is user friendly for all data setting.**

Optional Parts:

1. **Unwind Pick-Up Lift : For loading jumbo roll on the machine quickly and efficiently.**
2. **Web Guide : To keep web wound out at one position, choosing either E.P.C or L.P.C (printed web use)**
3. **Web Cut-Off Device: Manual circular blade cutting with auto glue coating for fast adherence.**
4. **Sheet Counter : It is used for counting printed papers.**

佳源工業股份有限公司
WEBTEC INDUSTRIES CO., LTD.
TEL:886-2-22992289 FAX:886-2-22991055
WEBSITE: www.webtec-hy.com
新北市五股區新北產業園區五權路 51 號
NO. 51, WU CHUAN ROAD, NEW TAIPEI INDUSTRIAL PARK,
WU KU DISTRICT, NEW TAIPEI CITY, TAIWAN, R.O.C.
E-MAIL: webtec@ms46.hinet.net