

TA SLITTER



Application : 2 shafts center type winding, suitable for slitting various label stocks, films & papers, etc.

Specification : Machine Width : 1.3M/1.6M Max. Unwind O.D : 1000mm
Rewind Core I.D : 77mm Min. Slitting Width : 50mm
Max. Rewind O.D: 600mm / 800mm Machine Speed : 250M / Min



Features:

1. Equipped with separated shaft type unwind base, auto web guide, splice table and auto unwind tension controller.
2. Driven by connective 3 A.C motors, which able to control tension on air shaft and linear speed on differential shaft.
3. Rewind type is as center winding, working with differential shaft to make the same tension on each finished roll to overcome uneven web thickness.
4. Rewind 600mm model is a connected unloading rack, and for the rewind 800mm is a separated type unloading rack.
5. Equipped with shear cutter, which is suitable for slitting various materials. Trim unit is a suction blower design power by A.C. motor control, which collects waste materials more efficiently.
6. All functions operate under LCD touch panel control, which is user friendly for all data setting.
7. Central system is controlled by PLC unit and all the electrical devices are conform to the latest European CE regulation for safety operation.

Optional Parts:

1. Unwind Pick-Up Lift : For loading jumbo roll on the machine quickly and time saving.
2. Special Unwind Base : Separated type with shaftless hydraulic core chuck can be equipped for efficient and quick performance on jumbo roll changing.
3. Rewind air shaft : For large sizes slitting and rewind.
4. Core Positioning Mold: This device helps to line up paper core in position much efficiently and precisely.



佳源工業股份有限公司
WEBTEC INDUSTRIES CO., LTD.

TEL:886-2-22992289 FAX:886-2-22991055
WEBSITE: www.webtec-hy.com

新北市五股區新北產業園區五權路 51 號

NO. 51, WU CHUAN ROAD, NEW TAIPEI INDUSTRIAL PARK,
WU KU DISTRICT, NEW TAIPEI CITY, TAIWAN, R.O.C.
E-MAIL: webtec@ms46.hinet.net